



US006368206B1

(12) **United States Patent**
Hunter et al.

(10) **Patent No.:** **US 6,368,206 B1**
 (45) **Date of Patent:** **Apr. 9, 2002**

(54) **BIOLOGICAL SAFETY CABINET WITH
 IMPROVED AIR FLOW**

(75) **Inventors:** Jim Hunter, Olathe; Kevin Gilkison, Overland Park, both of KS (US); Larry Nelson, Kingsville, MO (US); Burt Rhea, Overland Park, KS (US); Jerry O'Dell, Independence, MO (US); Greg Krueger, Trimble, MO (US); Gary Roepke, Kansas City, MO (US); Gerhard W. Knutson, Edina, MN (US); Mary Ellen Kennedy, Ashton (CA)

(73) **Assignee:** Labconco Corporation, Kansas City, MO (US)

(*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** 09/553,923

(22) **Filed:** Apr. 20, 2000

(51) **Int. Cl.⁷** B08B 15/02

(52) **U.S. Cl.** 454/58; 312/209; 454/57

(58) **Field of Search** 454/56, 57, 58;
 312/209

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,011,425 A * 12/1961 Grushoff 454/57
 3,254,588 A * 6/1966 Truhan 454/58
 3,318,076 A * 5/1967 Baker 454/56 X
 3,415,180 A * 12/1968 Arhex et al. 454/58

3,811,250 A * 5/1974 Fowler, Jr. 454/56 X
 3,895,570 A * 7/1975 Eagleson, Jr. 454/57
 4,548,627 A 10/1985 Landy
 5,050,943 A * 9/1991 Barnett
 5,295,902 A * 3/1994 Hock
 5,380,244 A * 1/1995 Tipton 454/57
 6,036,737 A * 3/2000 Smith et al. 454/58 X

FOREIGN PATENT DOCUMENTS

EP 0 486 971 A * 5/1992 454/56

* cited by examiner

Primary Examiner—Harold Joyce

(74) *Attorney, Agent, or Firm*—Shook, Hardy & Bacon

(57) **ABSTRACT**

A biological safety cabinet is provided that includes a frame. The frame defines a protected work area and encloses the work area on all but one side. A sash is coupled to the frame that at least partially encloses the side that is not enclosed by the frame. A blower is coupled to the frame generally above the work area to make the work area a negative pressure area so that harmful materials are confined. A sash grill is coupled to the frame generally below the sash that has a curved top surface. The curved sash grill provides a superior and less turbulent air-flow into the work area, thereby better containing any harmful materials. The curved sash grill is perforated, and the curvature and perforations of the sash grill compensate for partial blockage by such things as the user's arms and other objects. The curvature of the sash grill also avoids a sharp angle at the same height as the work surface which reduces the chance of contact and possible breakage of labware as it is moved into the cabinet.

26 Claims, 5 Drawing Sheets

